

- Sub-
G1
1. (Amended) An interrupt request controller for processing a plurality of interrupt logic signals, such controller, comprising:
- a programmable bit masking section fed by the interrupt logic signals, adapted to mask selected ones of the interrupt signals;
 - an interrupt section fed by the programmable mask section for coupling unmasked ones of the interrupt signals to a plurality of outputs selectively in accordance with a predetermined criteria, such predetermined criteria being established by a second mask.
- B
2. An interrupt request controller for processing a plurality of interrupt logic signals, such controller, comprising:
- a programmable section fed by the interrupt signals, for selecting assertion sense and/or assertion type of each one of the interrupt signals.
3. An interrupt request controller for processing a plurality of interrupt logic signals, such controller, comprising:
- a programmable section fed the interrupt signals, for storing a bit for each one of the interrupt logic signals representative of whether the logic state of the interrupt logic signal should be, or should not be, inverted and for producing a corresponding output logic interrupt signal in accordance therewith.
4. (Amended) An interrupt request controller for processing a plurality of interrupt logic signals, such controller, comprising:
- a programmable section fed the interrupt signals, for storing a bit for each one of the interrupt logic signals representative of whether the logic state of the interrupt logic signal should be an edge or remain as a level and for producing a corresponding output logic interrupt

signal in accordance therewith.

Sub C1 5. An interrupt request controller for processing a plurality of interrupt logic signals, such controller, comprising:

a programmable section fed by the interrupt signals, for selecting assertion sense and/or assertion type of each one of the interrupt signals;

a programmable bit masking section coupled to the programmable assertion sense/assertion type section, adapted to mask selected ones of the interrupt signals;

B an interrupt section fed by the programmable mask section for coupling unmasked ones of the interrupt signals to a plurality of outputs selectively in accordance with a predetermined criteria, such predetermined criteria being established by a second mask..

6. The interrupt request controller recited in claim 5 wherein the programmable assertion sense and/or assertion type section includes for each one of the interrupt logic signals an interrupt sense register for storing a bit representative of whether the logic state of the interrupt logic signal should be, or should not be, inverted.

7. The interrupt request controller recited in claim 6 wherein the programmable assertion sense and/or assertion type section includes for each one of the interrupt logic signals, an interrupt type register for storing a bit representative of whether the logic state of the interrupt logic signal should remain as an edge or be converted to a level.

8. (NEW) The interrupt request controller recited in claim 5 wherein the programmable assertion sense and/or assertion type section includes for each one of the interrupt logic signals, an interrupt type register for storing a bit representative of whether the logic state of the interrupt logic signal should remain as an edge or be converted to a level.